

Electrosurgical Unit Series 350 Reliability & Safety

- Owns memory function, reserves the last time used data.
- It has neutral electrode contact inspection system, which can detect electrode contact area, and system will test and evaluate the effective contact area between electrode and derma, if the contact area was found low to a danger level, system will automatic cutout and gives alarm indication.
- High definition large LED indication.
- Main unit has automatic monitoring function and mistake indication function.
- Endoscopy Connector
- Applications: general, thoracic, orthopedics, obs and gyn, urologic, cerebral, microsurgery, & ORL, ENT surgeries, etc.
- Automatic compensation function, stable output power, Can cut underwater (T.U.R.), including organic cut in rich fat area;



Model D



Model C

- The unit is Chinese Origin;
- The specifications may change without prior notice;

Technical Data

Advantages	Model C	Model D
Power Output	400W	350W (Optional 400W)
Output Modes	(6) Modes: Cut,Blend1,Blend2,Electro Coag1,Electro Coag2, Bipolar	(5) Modes: Cut,Blend1,Blend2,Electro Coag1,Electro Coag2,
Output Rating	A-Cut : 1 W~ 400 W (Load 800Ω) B-Blend1: 1W~200W (Load 800Ω) C-Blend2: 1W ~150W(Load 800Ω) D-Electro Coag.1:1W~120W(800Ω) E-Electro Coag.2:1W~100W(800Ω) F-Bipolar Coag.: 1W~70W (200Ω)	A-Cut : 1 W~ 350 W (Load 800Ω) B-Blend1:1W~200W (Load 800Ω) C-Blend2:1W ~150W(Load 800Ω) D-Electro Coag.1:1W~120W(800Ω) E-Electro Coag.2:1W~100W(800Ω)
Specifications	1-Ambient Temp. range:5C~40C; 3-Atmospheric pressure Range:86.0~106.0kpa 5- Operating Freq. : 330~460 KHz; 7-Type : CF	2- Relative Humidity Range: ≤80; 4-Power: 220V ±22V; 50HZ ±1; 6-Related power : 1100 VA ±10%
Power Consumption	≤1100VA (Cut Function 400)	
Transport & Storage	A-Ambient Temp. Range : - 40 C ~ 55 C; C-Atmospheric pressure : 500 hpa ~ 1060hpa	B- Relative Humidity : ≤95%
Leakage current for Grounding	Normal status ≤ 0.5 mA	
Leakage Current for shell	Normal status ≤0.1 mA	
Main Unit Dimensions	36.5x33x12,5 cm	34x29.5x13 cm
Net Weight	6.5 kg	6 kg
Package Size	46x42x30 cm	43.5x38.5x31 cm
G. Weight	10.5 kg	10 kg
Standard Accessories	Main unit (1pc);Double Footswitch(1pc); ESU Pencil(2pc);Electrode(Disposable)(1pc); Bipolar forcep(1pc);Bipolar forcep cable(1pc); Electrode cable(1pc); power cable(1pc);Fuse(2pc); User manual(1pc);packing list(1pc); Guatantee card(1pc);	Main unit (1pc);Double Footswitch(1pc);ESU Pencil(2pc);Electrode(Disposable)(1pc); Electrode cable(1pc);power cable(1pc); Fuse(2pc);User manual(1pc); packing list(1pc); Guatantee card(1pc);